



Power Soak LS-150

ALKALINE STEEL CLEANER

LS-150 is a high solids alkaline barrel process surface renovator detergent. An advance heavy duty soak cleaner for use in metal operations processing steel. Can be used in metal tumbling and vibratory finishing operations or other heavy duty soak tanks.

LS-150 is can also be used in barrel plating lines as both soak and barrel electro cleaner and as a soak cleaner in rack plating operations, barrel processing operations where heavy duty degreasing and cleaning is required. Non-phosphated workhorse cleaner. Helps to lift light scale, oxides and resistant films.

LS-150 attacks difficult lubricants, greases, oils, light rust, light scale, and oxides. Offering advanced detergency and film free rinsing. Effectively manages oils for long effective solution life.

Features & Benefits

- High solids liquid
- Non-Phosphated
- Biodegradable
- Providing efficient surface cleaning at low cost
- Film free rinsing with superior “anti-redeposition” properties
- Ease of control by simple titration
- Easy to automatic feed
- Never dump operating procedures
- Extended use and operating procedures to eliminate costly dumping
- Does not contain glycol ethers or solvent materials

Physical Data

pH	13
Product Type	Liquid
Spec. Gravity	1.195
lbs./gal.	9.97
Foam, 0 = Low, 9 = High	9
Shelf-Life Years	10 years
Freeze Information	Not damaged by freezing



Typical Processing

Soak Cleaning

1. Concentration: 4-12%
2. Time: 4-8 minutes
3. Temperature: 120-180 F
4. Agitation: (3-5 RPM in barrels)

Tumbling Barrels: (Deburring, Burnishing, Degreasing)

1. Concentration: 1-5%
2. Time: 1/2-several hours.
3. Temperature: cool - warm
4. Agitation: Barrel

Electro Cleaning:

1. 6-10% by volume
2. Temperature: 140-200 F.
3. Volts = 5-7
4. AMPS = 10-50 per square foot
5. Time: 90-240 seconds or per programmed system

Packaging

Container Type	Poly
Net Units	545
Tare Wt.	25 lb.
Gross Wt.	570
DOT_Name	UN 1824, Sodium Hydroxide Solution, 8, PG II
DOT Hazard	Corrosive
Tarriff ID	2815.12

Use Parameters

Concentration Range	6-10%
Temperature Range	90-200 F.
Time Range	2-12 minutes
Agitation	Rotation or mechanical

Waste Disposal

Neutralize pH, removes heavy metals, fats, oils, and grease.



Holding Tank Materials of Construction

Steel, stainless, or poly.

Other Information

It is important that the OSHA DATA, "Material Safety Data Sheet" be carefully read and reviewed with the users of this product. OSHA data is required to be posted in the work area by law.

WARRANTY: HUBBARD-HALL INC. IS NOT RESPONSIBLE FOR THE MISUSE, MISAPPLICATION, OR MISHANDLING OF THIS PRODUCT. SEE THE TERMS AND CONDITIONS OF SALE ON OUR WEBSITE FOR ADDITIONAL TERMS AND CONDITIONS CONCERNING OUR PRODUCTS, INCLUDING BUT NOT LIMITED TO, LIMITATIONS AND DISCLAIMERS OF WARRANTIES AND LIABILITIES.

Our People. Your Problem Solvers.

For more information on this process,
please call us at 203.756.5521 or email: techservice@hubbardhall.com

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**¹³⁶.